



SafeLifting.eu
Your **Rental** Partner

SafeLifting Europe B.V.

Benelux Workpark
Schiedamsedijk 54L, 3134 KK Vlaardingen
The Netherlands
P.O Box 239, 3130 AE Vlaardingen
Tel: + 31(0) 10 434 63 33
24h: +31(0) 654 78 63 97
rental@safelifting.eu
www.safelifting.eu

60t Spooler

Technical data

Length:	7580mm
Width:	2435mm
Height:	2815mm
Max Reel Dia:	4000mm
Max Reel Width:	4000mm
Machine weight:	15.000Kg Without shaft
Lifting:	Fitted with forklift pockets & 4 point lifting sling set fitted (without reel).
Design Temperature:	-10° up to +40°C

Performance Data

Low Speed

Layer Diameter (mm)	Pull @ 250 bar (Tonnes)	Winch Speed (M/Min)
500	25	23
1000	12.5	46
1500	8.35	69
2000	6.25	92
2500	5	115
3000	4.15	138
3500	3.55	161
4000	3.10	184

High speed

Layer Diameter (mm)	Pull @ 250 bar (Tonnes)	Winch Speed (M/Min)
500	12.5	46
1000	6.25	92
1500	4.15	138
2000	3.1	184
2500	2.5	230
3000	2	276
3500	1.75	322
4000	1.55	368

Safer Smarter Greener

